

# CRUSTEX & HYDROMULCHING

CRUSTEX is a heavy duty film forming compound which, when used as an additive in hydromulch mixtures, greatly improves the strength and durability of resultant stabilised surface.

## ADVANTAGES OF USE OF CRUSTEX IN CONJUNCTION WITH HYDROMULCH

1. Dramatically increased resistance to short and long term deterioration processes caused by pedestrian traffic, vehicles, wind and water erosion.
2. Non staining to the environment. CRUSTEX does not change the appearance of the mulch thereby allowing easy colouring of the mulch if such colouring is aesthetically desirable.

## USEAGE RATE

CRUSTEX should be diluted at the rate of 1 : 50 to 1 : 100 in the tank used to prepare the mulch to be sprayed (prior to addition of paper or wood pulp). The application rate will thus be approximately 150 - 250 litres per hectare.

## IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. ALWAYS TEST FIRST.*