

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | **FREE** 1800 999 196 | F +61 8 9302 5000

Page 1 of 3

Date of Issue: 25/09/2019

Last revision: November 2016

File F:\TECHBULL\Techbull-current\LinkSeal.docx

LINK SEAL 30 FLOOR SEALER / FINISH FOR LINOLEUM, TERRAZZO & VINYL

LINK SEAL 30


LINK SEAL 30 is an acrylic sealer finish for linoleum, terrazzo and vinyl floors.

LINK SEAL 30 has been formulated with specialty wax compounds to minimise black heel marking and scuffing. Further applications and buffing of LINK SEAL 30 will produce a higher gloss.

DIRECTIONS: LINK SEAL 30 should be applied without diluting using a new lint free cotton or poly cotton mop. 2 or 3 thin coats are required depending on traffic to which the surface is to be subjected. Allow 20 minutes between coats. Do not use if temperature is below 10oC or relative humidity is above 85% - film formation will not occur and the coating will fail.

FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor (at once).

BATCH NO. ??????????



CONTENTS ???? L

ENVIRONEX INTERNATIONAL

T: +61 8 9302 4000 E : sales@environex.net.au

F: +61 8 9302 5000 W: www.environex.net.au

FREE 1800 999 196 19 Motivation Drive, Wangara, WA 6065

MATERIAL & FUNCTION

LINK SEAL 30 is a new generation acrylic sealer finish for the sealing of linoleum and vinyl floors. **LINK SEAL 30** is formulated to eliminate the need for a base prime coat to

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

Page 2 of 3

Date of Issue: 25/09/2019

Last revision: November 2016

File F:\TECHBULL\Techbull-current\LinkSeal.docx

be applied prior to use of normal topcoats for linoleum and vinyl.

LINK SEAL 30 is a higher solids version of **LINK SEAL 22** where a heavier film build is required to provide a more durable wearing surface, which thereby reduces the time between stripping and recoating.

LINK SEAL 30 is formulated with specialty wax compounds to minimize black heel marking and scuffing. The metal linked acrylic base polymers have been selected to produce maximum gloss, depth of colour and endure heavy traffic conditions giving excellent wear and durability. **LINK SEAL 30** will respond to buffing to promote a harder wearing, higher gloss surface, although this is not essential.

LINK SEAL 30 also finds application as a wear coat over slate surfaces which have been sealed with **ENDURE** as manufactured by **ENVIRONEX** International.

For extra durability **LINK SEAL 30** can be applied over a sealer coat such as **ENDURE** where extremely high traffic is encountered.

APPEARANCE

White, milky, water thin liquid.

APPLICATION

LINK SEAL 30 should be applied without diluting using a new lint free cotton or poly cotton mop.

Two or three applications are required depending on the traffic to which the surface is to be subjected. Thin applications are preferable to heavy applications and each coat should ideally be applied at a 90° angle to the previous coat to ensure evenness of final film.

Approximately 15 - 20 minutes between coats should be allowed depending upon temperature and humidity. (Do not use if temperature is below 10°C or relative humidity is above 85% - film formation will not occur and the coating will fail).

LINK SEAL 30 is not suitable for high speed buffing (2000 rpm machines).

For maintenance cleaning use **DUBL CLEAN**. For removal use **CYCLONE**.

PACKAGING

5 Litre, 15 Litre and 200 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for

TECHNICAL BULLETIN



19 Motivation Dve Wangara, WA, 6065 AUSTRALIA
T +61 8 9302 4000 | **FREE** 1800 999 196 | F +61 8 9302 5000

Page 3 of 3

Date of Issue: 25/09/2019

Last revision: November 2016

File F:\TECHBULL\Techbull-current\LinkSeal.docx

*any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST***